

SSI™ NIPPLE TYPE TUBE DIFFUSERS

AFTS21000 62mm Tube



- Highest possible quality and technology means years of trouble-free efficient operation.
- Highest possible SOTE independently tested per ASCE and lowest possible headloss.
- Compression molded EPDM membranes have very tight wall thickness tolerances, a long track record and exhibit even air distribution and minimal shrinkage over time.
- One-piece lightweight but strong ABS body makes handling during installation very easy.
- Single orifice on top center line of pipe means little chance for a single diffuser failure to contaminate all diffusers.
- Experienced Engineering and Drafting staff with years of practice to assist you.
- Integral register prevents cantilevered diffusers from axial rotation around the header pipe.
- 212° F (100° C) temperature resistance and environmentally-friendly ABS body.
- Individual thermocouples in each cavity of compression mold = 100% quality control.
- Low membrane plasticizer content to reduce shrinkage and hardening, but enough to avoid creep.
- Multiple integral check valves keep your aeration piping system clean.
- In stock on 3 continents in 4 locations.

TUBE MEMBRANES


WEBBED URETHANE

PTFE DISPERSION

EPDM

ANTI-STATIC EPDM

fEPDM



21st century special materials such as PTFE-coated surface layers, fEPDM, anti-static EPDM, webbed urethane, as well as reinforced and coated ultra fine bubble membranes, offer outstanding chemical and fouling resistance, in addition to the highest oxygen transfer efficiency at a headloss you can live with.

Please see reverse for additional technical data






STAMFORD SCIENTIFIC
INTERNATIONAL
INCORPORATED

+1-845-454-8171 TEL
+1-845-454-8094 FAX

4 TUCKER DRIVE
POUGHKEEPSIE, NEW YORK 12603 USA
www.StamfordScientific.com
EMAIL: INFO@STAMFORDSCIENTIFIC.COM

SSI™ NIPPLE TYPE TUBE DIFFUSERS *continued*

AFTS21000 62mm Tube



DESIGN FLOW PER METER	FLOW RANGE PER METER	ACTIVE SURFACE AREA	WEIGHT
0.75 – 4.25 SCFM (1.3 – 7.25 Sm ³ /hr)	0 – 5.5 SCFM (0 – 9.0 Sm ³ /hr)	1.625 ft ² (0.15 m ²) /Diffuser	3.0 lbs (1.4 Kg) /Diffuser



STAMFORD SCIENTIFIC
INTERNATIONAL
INCORPORATED

+1-845-454-8171 TEL
+1-845-454-8094 FAX

4 TUCKER DRIVE
POUGHKEEPSIE, NEW YORK 12603 USA
www.StamfordScientific.com
EMAIL: INFO@STAMFORDSCIENTIFIC.COM